





OA200/400/600 Series Overall Dimention
And Performance Parameter


The Standard Type



The direct Type



Parameters of The direct Type		
	OA 20	OA40/60
Square	□14x14, □17x17	□17x17, □22x22
Flange	F07, F10	
Stem	Height≤25mm	



Parameters	Type	OA 200				OA 400				OA 600			
	Power	DC24V	AC110V	AC380V	AC220V	DC24V	AC110V	AC380V	AC220V	DC24V	AC110V	AC380V	AC220V
Performance													
Motor Power		35W	40W	30W	40W	70W	90W	40W	90W	70W	90W	40W	90W
Rated Current		3.57A	0.65A	0.15A	0.37A	5.13A	1.12A	0.29A	0.57A	6.04A	1.18A	0.29A	0.60A
Standard Time/Torque		30S/200Nm				30S/400Nm				45S/600Nm			
Optional Time/Torque		15S/100Nm			15S/100Nm 60S/200Nm	15S/100Nm			15S/100Nm 60S/200Nm				
Turning Angle		0~90° at any angle											
Available Control Circuit		Type A/B/C/D/E/F/G/H											
Total Weight		8.0kg				8.5kg				9.0kg			
Insulating Resistance		DC24V/AC24V:100MΩ/250VDC AC110V/AC220V/AC380V:100MΩ/500VDC											
Withstand Voltage Class		DC24V/AC24V:500VAC 1minte、AC110V/AC220V:1500VAC 1minte、AC380V:1800VAC 1minte、											
Protection Class		IP 67											
Installation Angle		360° at any angle											
Electric Interface		G1/2 waterproof cable connector: the power cord, signal lines each one											
Ambient Temperature		-30℃ ~ +60℃											
Supply function		Pretection for over-torque dehumidification wet heater											